

Incomaster

Incontinence Waste Disposal

Fast, efficient and safe disposal of incontinence waste and sanitary pads — **Incomaster** is trusted by thousands of care facilities around the world to reduce the risks, issues and costs associated with bags of waste.



HYGIENIC - SIMPLE - ECONOMICAL

Hygienic

Getting rid of resident waste as soon as possible rather than bagging and carrying around

- ✓ Reduces unpleasant odours on site
- ✓ Reduces infection risk to staff and residents
- ✓ Helps keep rooms clean and tidy

The Incomaster also incorporates a santitisation cycle to assist with your cleaning standard operational procedures.



Haigh's unique cutting system ensures that large particles do not enter your drainage system

Convenient

Incomaster is designed for ease of use:

- ✓ Minimal user training required
- ✓ Touch free opening
- ✓ Automatic Start
- Easy-wipe surfaces with embedded antimicrobial

The **Incomaster** builds on Haigh's decades of experience designing and building the best macerators based on the metrics that matter the most to our customers

- ✓ Fastest
- ✓ Quietest
- ✓ Smallest

Economical

Incontinence waste from patients typically costs in the region of £912.00 per resident per year* using yellow bag systems.

Typical water and energy costs for **Incomaster** on a like for like basis are approximately £15.00 per annum.

A range of maintenance and leasing agreements are available to ensure your overall costs are compelling, with clients reporting overall savings of **up to 65%**.

"WE DON'T KNOW WHAT WE WOULD DO WITHOUT OUR INCOMASTER"

"THE SMELLS FROM BAGS WERE GONE FROM THE DAY WE INSTALLED IT"

Smart Systems

Internet enabled** to give you:

- ✓ Daily Usage report
- ✓ Energy and Water usage
- ✓ Smart Maintenance capabilities

Base your maintenance on actual usage rather than rely on traditional fixed schedules.

- ✓ Increases up-time
- ✓ Decreases running costs
- ✓ No complicated set-up
- * £1.00 per kg x 2.5 kg per patient per day x 365 days
- $\ensuremath{^{**}}$ remote monitoring option, subject to terms and conditions

01989 763131 info@haigh.co.uk

Technical Performance

Cycle Characteristics: 96 seconds | Touch Free Open | Sanitization Cycle | 4 kg load Water: 26 litres per cycle used | 5.5 litres per minute cold water Electricity: 1300 W motor | < 0.01 kWh per cycle | 230V / or 400V

Inlet, Outlet & Cistern: 3/4" BSP Inlet | 2" BSP multi-fit P-trap Outlet

Metrics: W: 432 mm | H: 946 mm | D: 607 mm | Dry Weight: 83 kg

















DOCREF - IM2018004/DRAFT